

Mobile generator sets HAC440GT

Set Model: GSC440GT

Prime power/capacity (kw/kva):400/500	Stable voltage regulation:≤±1%
Standby power/capacity (kw/kva): 440/550	Voltage fluctuation: ≤±0.5%
Power factor: : COSΦ=0.8	Transient voltage regulation: +20%~-15%
Rated output voltage (V): 400/230	Stable voltage time (s): ≤1
Rated current (prime/standby)(A):721.6/793.8	Stable frequency regulation: ≤±1%
Rated speed (rpm):1500	Frequency fluctuation: ≤±0.5%
Rated frequency (Hz):50	Transient frequency regulation: +10%~-7%
Start:Auto/Recoil	Stable frequency time (s): ≤3
Fuel:0#	Oil consumption (100% loading)(g/kwh):203
N.W.(kg):6000	Noise(7m)(dB):80
Demension(mm): 3650x1300x2850	

Diesel Engine

Brand: Cummins	Start: DC24V-electronic
producing area: Chongqing,China	Cooling: enclosed water cycle
Model: KTA19-G4	Oil supply: DI
cylinder: 6	Speed regulation: electron
Borexstroke(mm): 159x159	Air suction:TCI
Compression ratio: 14.5:1	Overload capacity: 110%
Structure:in-line	Rotate speed(rpm): 1500

Alternator

Brand: Marathon	Insulation class: H
Producing area:Shanghai	Protection grade: IP21



National HI-TECH Industrial & Development Zone, Zhengzhou, China
Tel: 0086-371-86525099

www.hamacpower.com

Model: MP-400-4A/S

Wiring:3-phase,4-wire,Y

Rated power(kw/kva): 400/500

Voltage regulation:DVR

Rated voltage(v):400/230

Output frequency(Hz):50

Power factor: COS Φ =0.8

HAMAC