

Soundproof diesel generator HAC75GS



Note: The photo of generator is only for your reference.

HAMAC

Model: HAC75GS

Prime power/capacity (kw/kva):68/85

Stable voltage regulation: $\leq \pm 1\%$

Standby power/capacity (kw/kva):75/93.8

Voltage fluctuation: $\leq \pm 0.5\%$

Power factor: : $\text{COS}\Phi=0.8$

Transient voltage regulation: +20%~-15%

Rated output voltage (V): 400/230

Stable voltage time (s): ≤ 1

Rated current (prime/standby)(A):122.7/135.3

Stable frequency regulation: $\leq \pm 1\%$

Rated speed (rpm):1500

Frequency fluctuation: $\leq \pm 0.5\%$

Rated frequency (Hz):50

Transient frequency regulation: +10%~-7%

Start:Auto/Recoil

Stable frequency time (s): ≤ 3

Fuel:0#

Oil consumption (100% loading)(g/kwh):214

N.W.(kg):1650

Noise(7m)(dB):70



Dimension(mm): 2690x950x1370

Diesel Engine

Brand: Cummins

Start: DC24V-electronic

producing area:Xiangfan,China

Cooling: enclosed water cycle

Model: 6BT5.9-G2

Oil supply: DI

cylinder:6

Speed regulation: electronic

Borexstroke(mm): 102x120

Air suction:TCI

Compression ratio: 17.5:1

Overload capacity: 110%

Structure:V

Rotate speed(rpm): 1500

Alternator

Brand: Marathon

Insulation class: H

Producing area:Shanghai

Protection grade: IP21

Model: MP-70-4

Wiring:3-phase,4-wire,Y

Rated power(kw/kva): 70/87.5

Voltage regulation:DVR

Rated voltage(v):400/230

Output frequency(Hz):50

Power factor: COS Φ =0.8